

Cardiac  
Arrest  
Registry to  
Enhance  
Survival

# CARES

## Version 3.3.4/3.4.0

### Data Dictionary

***LAST UPDATED – 11/2024 (v1.90)***

***Get the latest vendor resources @ <https://vendors.mycares.net>***

The CARES Dataset, Version 3.0 is composed of three separate components. 1) A First Responder Dataset provides a standardized set of definitions describing a First Responding Agency event for a Cardiac Arrest event. 2) An EMS Dataset provides a standardized set of definitions describing an EMS event. 3) A Hospital Dataset provides a standardized set of definitions describing a Hospital event.

**Any implementation of the CARES Version 3.0 dataset must include the use of the EMS dataset, and XML standard.**

Information provided in this document includes the following:

- ☐ Name of the Data Element
- ☐ Definition of the Data Element
- ☐ Data Type of the Data Element (many data elements have comments provided to assist in the implementation of a database schema)
- ☐ How to deal with missing or incomplete information (See Missing Data or Null Values below)
  
- ☐ **Notes:**
  - *Constraints - the constraints reflected in the fields in this document are meant to correspond to CARES constraints. See the NEMSIS definitions [www.nemsis.org](http://www.nemsis.org) for more detailed element information.*
  - *There may be more than one NEMSIS code mapped to a CARES field in enumerated elements. For instance, more than one NEMSIS code might map to CARES “Other” field as specified in the element definitions.*
  - *If a dateTime field has no time component, such as Date of Birth, use dateTime format and pass in midnight (all zeroes).*
  - *NOT Values are ignored by CARES unless its use is specifically noted on an element’s page.*

#### **PARSING NOTES**

***If an XML file contains an incident that already exists in CARES for the agency based on its eRecord.01, it will not be imported. If the same incident eRecord.01 recurs inside of a single submission, only the first occurrence will be imported.***

***If an incident was already entered directly in CARES with the same Date of Arrest and Incident Number for a given agency (based on eArrest.14 or eTimes.03 and eResponse.03), the XML incident will not be imported.***

# Cardiac Arrest Registry to Enhance Survival (myCARES) Dataset

## Table of Contents

<b>Header</b>	
General Information	1
<b>EMS Dataset</b>	
Call Information	15
Arrest Information	40
Resuscitation Information	47
First Cardiac/ROSC Information	59
Times Information	65
Hypothermia Information	83
EMS Interventions	86
<b>Hospital Dataset</b>	
Hospital Information	106

# ***Header***

## ***General Information***

## EMS Agency Unique State ID

dAgency.01

### Definition

The unique ID assigned to the EMS Agency which is associated with all state licensure numbers and information.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Mandatory	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

This value must match the value set in the myCARES agency profile configuration.

## EMS Agency Number

dAgency.02

### Definition

The state-assigned provider number of the responding agency.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Mandatory	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

15

### Data Element Comment

This value must match the value set in the myCARES agency profile configuration.

This is the primary identifier for the entire Demographic Section. Each of the Demographic sections must be associated with an EMS Agency Number. An EMS Agency can have more than one Agency Number within a state. This reflects the ability for an EMS Agency to have a different number for each service type or location (based on state implementation). The EMS Agency Number in dAgency.02 can be used to auto-populate eResponse.01 EMS Agency Number in the EMS Event section.

## EMS Agency State

dAgency.04

### Definition

The state/territory which assigned the EMS agency number.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>	<b>D01_0</b>	<b>Is Nillable</b>	No
<b>Usage</b>	Mandatory	<b>Recurrence</b>	1:1

### Constraints

#### Pattern

[0-9]{2}

### Data Element Comment

This value must match the value set in the myCARES agency profile configuration.

This has been clarified to reflect that it is the state in which the EMS Agency resides and the state associated with the EMS Agency number.

## Import Version

eCustomConfiguration.ImportVersion

### Definition

The version of the import specification used to create this file.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
3.0	Import Version

### Data Element Comment

This value should always be 3.0.



## Import Method

eCustomConfiguration.ImportMethod

### Definition

The method to use during the import.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Import
9	Testing – Do Not Import

## Software Used to Create This File

eRecord.03

### Definition

The name of the software used to create this file.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>	E01_03	<b>Is Nillable</b>	No
<b>Usage</b>	Mandatory	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

This is the EMS Agency's software, not the state or other level software, which electronically received the data from the local EMS Agency.

## Software Version

eRecord.04

### Definition

The version of the application used to create this record.

National Element	Yes	Pertinent Negatives (PN)	No
State Element	Yes	NOT Values	No
Version 2 Element	E01_04	Is Nillable	No
Usage	Mandatory	Recurrence	1:1

### Constraints

**Data Type**  
String

**minLength**  
1

**maxLength**  
50

## Developer Contact Last Name

eCustomConfiguration.ContactLastName

### Definition

The Last Name of the primary developer of the export file.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
String

**minLength**  
1

**maxLength**  
50

## Developer Contact First Name

eCustomConfiguration.ContactFirstName

### Definition

The First Name of the primary developer of the export file.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
String

**minLength**  
1

**maxLength**  
50

## Developer Contact Phone #

eCustomConfiguration.ContactPhone

### Definition

The phone number of the primary developer of the export file

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required	Recurrence	1:1

### Constraints

**Data Type**  
String

**minLength**  
10

**maxLength**  
10

## Developer Contact Email

eCustomConfiguration.ContactEmail

### Definition

The email of the primary developer of the export file.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
String

**minLength**  
9

**maxLength**  
50

# ***EMS Dataset***

## ***Call Information***



## Date of Arrest (NEMESIS 3.3.4, 3.4.0)

eCustomConfiguration.servicedate

### Definition

The date of the cardiac arrest.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

date

#### minInclusive

1950-01-01

#### maxInclusive

2050-01-01

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}

OR

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

If none is passed and eArrest.14 is nil, the date value from eTimes.03 will be used. This will produce a Warning if absent with eArrest.14.

Date consists of finite-length characters of the form: yyyy '-' mm '-' dd

## Date of Arrest (NEMESIS 3.3.4, 3.4.0)

eArrest.14

<b>Definition</b> The date of the cardiac arrest.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMESIS) No (CARES)
<b>Version 2 Element</b>	E11_08	<b>Is Nillable</b>	Yes (NEMESIS) No (CARES)
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
dateTime

**minInclusive**

1950-01-01T00:00:00-00:00

**maxInclusive**

2050-01-01T00:00:00-00:00

### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

If none is passed and custom element servicedate is nil or missing, the date value from eTimes.03 will be used. This element is a component of the Utstein Cardiac Arrest Criteria as identified in the American Heart Association journal "Resuscitation" from 2004 entitled "Cardiac Arrest and Cardiopulmonary Resuscitation Outcome Reports". <http://circ.ahajournals.org/cgi/content/full/110/21/3385>

Changed from estimated time prior to EMS arrival to date/time of cardiac arrest.

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
'-' separators between parts of the date portion  
mm a two-digit numeral that represents the month  
dd a two-digit numeral that represents the day  
T separator that indicates time-of-day follows  
hh a two-digit numeral that represents the hour  
':' a separator between parts of the time-of-day portion  
mm a two-digit numeral that represents the minute  
ss a two-integer-digit numeral that represents the whole seconds  
'.' s+ (not required) represents the fractional seconds  
zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
mm a two-digit numeral that represents the minutes  
'+' a nonnegative duration

## Incident Number

eResponse.03

### Definition

The incident number assigned by the 911 Dispatch System.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E02_02	<b>Is Nillable</b>	Yes (NEMSIS) No (CARES)
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
String

**minLength**  
3

**maxLength**  
NEMSIS 3.3.4 - 32  
NEMSIS 3.4.0 - 50

### Data Element Comment

The combination of Date of Arrest and Call Number must represent a unique event. **myCARES does not accept Not Values or Nil for this field. An Incident Number must be present in every Patient Care Report.**

## Booklet ID

eCustomConfiguration.BookletID

### Definition

The myCares.net™ HealthEMS™ booklet number associated to this event.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

**Data Type**  
Integer

**minLength**  
5

**maxLength**  
10

### Data Element Comment

Vendors can omit this element from their XML altogether. The only uses would be for HealthEMS™ users who choose to fill out the CARES form instead of the HealthEMS™ form and need to enter the HealthEMS™ BookletID on the CARES form to later match to a HealthEMS™ record to retrieve additional information. This field would then help assist that process. This will be used to help auto-match this information to the corresponding CAD information.

## EMS Response Number

eResponse.04

### Definition

The internal EMS response number which is unique to each EMS vehicle's response to an incident within an EMS agency.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### minLength

3

#### maxLength

50

### Data Element Comment

This number can be passed as additional incident identifier.

## Incident Address

eScene.15

### Definition

The street address where the incident occurred.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E08_11	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Required (CARES)	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

255

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Incident City

eScene.17

### Definition

The city where the incident occurred.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E08_12	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Required (CARES)	<b>Recurrence</b>	0:1

### Data Element Comment

City codes are based on GNIS Feature Class. The primary Feature Class to use is "Civil" with "Populated Place" and "Military" code as additional options.

Definitions for each GNIS City Feature Class can be found on the GNIS Codes website.

GNIS Codes Website: [http://geonames.usgs.gov/domestic/download\\_data.htm](http://geonames.usgs.gov/domestic/download_data.htm)

## Incident City (3.3.4 only)

eCustomConfiguration.IncidentCityStr

### Definition

Field used to pass a text/string value for Incident city.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>		<b>Recurrence</b>	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

This is an optional element for vendors that cannot pass GNIS codes for eScene.17. This element will take precedence over eScene.17 if there is a value passed in both elements. Can be omitted from XML if not used. Example: Cincinnati.



## Incident State ID

eScene.18

### Definition

The state where the incident occurred.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E08_14	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### length

2

### Data Element Comment

Based on the ANSI State Code.

GNIS Codes Website: [http://geonames.usgs.gov/domestic/download\\_data.htm](http://geonames.usgs.gov/domestic/download_data.htm)

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Incident Zip Code

eScene.19

### Definition

The zip code where incident occurred.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E08_15	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

#### Pattern

[0-9]{5}||[0-9]{5}-[0-9]{4}||[0-9]{5}-[0-9]{5}||[A-Z][0-9][A-Z] [0-9][A-Z][0-9]

### Data Element Comment

ZIP Codes Product Website: <https://www.zipcodedownload.com/Products/Product/Z5Commercial/Standard/Overview/>  
Product: USA - 5-digit ZIP Code Database, Commercial Edition.

**\*\*CARES REQUIRED FIELD IN 2012\*z**

## Incident County ID

eScene.21

### Definition

The FIPS County code where incident occurred.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E08_13	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

<b>Data Type</b>	<b>length</b>
String	5

### Data Element Comment

Based on the ANSI Code. Single Choice based on the County Name but stored as the ANSI code (combined 5 digit State and County codes). Should be required if there is a patient associated with the event. 5 digits can be passed with leading zeroes up to the county code.

GNIS Codes Website: [http://geonames.usgs.gov/domestic/download\\_data.htm](http://geonames.usgs.gov/domestic/download_data.htm)

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient First Name

ePatient.03

### Definition

The patient's first name.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_02	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Required (CARES)	<b>Recurrence</b>	0:1

### Attributes

#### Pertinent Negatives (PN)

8801019 – Refused      8801023 - Unable to Complete

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient Last Name

ePatient.02

### Definition

The patient's last name.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_01	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Required (CARES)	<b>Recurrence</b>	0:1

### Attributes

#### Pertinent Negatives (PN)

8801019 – Refused      8801023 - Unable to Complete

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient Age

ePatient.15

### Definition

The patient's age.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_14	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

Integer

#### minInclusive

1

#### maxInclusive

120

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient Age Units

ePatient.16

### Definition

The unit used to define the patient's age.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_15	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
2516001	Days
2516003	Hours
2516005	Minutes
2516007	Months
2516009	Years

### Data Element Comment

Hours and Minutes will be calculated into days by CARES parsing.

## Patient Date of Birth

ePatient.17

### Definition

The patient's date of birth.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_16	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Required (CARES)	<b>Recurrence</b>	1:1

### Attributes

#### Pertinent Negatives (PN)

8801019 – Refused      8801023 - Unable to Complete

### Constraints

#### Data Type

date

#### minInclusive

1890-01-01

#### maxInclusive

2050-01-01

### Data Element Comment

Valid date. To indicate an unknown DOB, please send 1890-01-01 or use custom DOB\_Unknown field.

```
<eCustomResults.ResultsGroup>  
  <eCustomResults.01>1</eCustomResults.01>  
  <eCustomResults.02>DOB_Unknown</eCustomResults.02>  
</eCustomResults.ResultsGroup>
```

**\*\*Either DOB OR DOB Unknown is REQUIRED by CARES IN 2012\*\***



## Patient Gender

ePatient.13

### Definition

The patient's gender.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E06_11	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
9906001	Female
9906003	Male

### Data Element Comment

Other NEMSIS code list values are not parsed by myCARES.

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient Race/Ethnicity

ePatient.14

### Definition

The patient's race/ethnicity.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes
<b>Version 2 Element</b>	E06_12	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:M

### Attributes

#### NOT Values (NV)

7701001 - Not Applicable      7701003 - Not Recorded

### Code List

Code	Description
2514001	American Indian or Alaska Native
2514003	Asian
2514005	Black or African American
2514007	Hispanic or Latino
2514009	Native Hawaiian or Other Pacific Islander
2514011	White

### Data Element Comment

The patient's ethnicity.

As of December 2017, either Not Value will map to the myCARES "Unknown" value. The custom element described below is still available, but will be removed in the future in favor of passing a Not Value:

This field is extended by custom element EthnicityUnknown- code = 8. To pass "Unknown" value, extend this field and pass proper value in custom element EthnicityUnknown.

<ePatient.14 CorrelationID="ePat" xsi:nil="true" NV="7701001"/><!--passing other-->

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Patient Ethnicity Unknown

eCustomConfiguration.EthnicityUnknown

### Definition

Field used to pass “Unknown” value for Ethnicity – extended field ePatient.14

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional (NEMESIS) Required (CARES, if applicable)	<b>Recurrence</b>	0:1

### Code List

Code	Description
8	Unknown

### Data Element Comment

This field will be removed in early 2018. Please just pass either Not Value in ePatient.14, which now maps to “Unknown” in myCARES.

Field used to pass “Other” value for Ethnicity – extended field ePatient.14

The patient’s ethnicity. This field is extended by custom element EthnicityUnknown- code = 8. To pass “Unknown” value, extend this field and pass proper value in custom element EthnicityUnknown.

<ePatient.14 CorrelationID="ePat" xsi:nil="true" NV="7701001"/><!--passing other-->

```
<eCustomResults.ResultsGroup>
<eCustomResults.01>8</eCustomResults.01>
<eCustomResults.02>EthnicityUnknown</eCustomResults.02>
<eCustomResults.03>ePat</eCustomResults.03>
</eCustomResults.ResultsGroup>
```



## Medical History

eHistory.08

### Definition

The patient's pre-existing medical or surgical history.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes
<b>Version 2 Element</b>	E12_10	<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended	<b>Recurrence</b>	0:M

### Attributes

#### NOT Values (NV)

7701001 - Not Applicable

7701003 - Not Recorded

#### Pertinent Negatives (PN)

8801015 - None Reported

8801019 – Refused

8801023 - Unable to Complete

8801021 – Unresponsive

### CorrelationID

#### Data Type

String

#### minLength

0

#### maxLength

255

### Attributes

#### Pattern

([A-QSTZ][0-9]{2})(\.[0-9A-Z]{1,3})?

### Code List (accepted by CARES)

#### Code

8801015

#### Description

No (Pertinent Negative)

8801023

Unknown (Pertinent Negative)

ICD-10 starts with C00-C99, D00-D99\*, R97

Cancer

ICD-10 starts with E08-E13

Diabetes

ICD-10 starts with I05-09, I20-27, I30-I52, I95, Q20-24, Z95

Heart Disease

ICD-10 starts with E78

Hyperlipidemia

ICD-10 starts with I10-16

Hypertension

ICD-10 starts with N00-08, N10-19

Renal Disease

ICD-10 starts with J12, J40-47, J80-86, J90-99

Respiratory Disease

or is B97.21 or B97.4

ICD-10 starts with I60-63, I69

Stroke

### Data Element Comment

Any other eHistory.08 value will map to "Other". Please pass text of what other is in MedHistoryOtherStr.

\*D49.9 will not import as Cancer.

To pass "Other" value, extend this field like the example below and pass the value in MedHistoryOther  
<eHistory.08 CorrelationID="eHist" xsi:nil="true" NV="7701001"/>

\*\*\*SUPPLEMENTAL\*\*\*

## Medical History Other

eCustomConfiguration.MedHistoryOther

### Definition

Field used to pass “Other” value for Medical History Other - which checks the “Other” checkbox in the CARES form.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
99	Other

### Data Element Comment

```
<eCustomResults.ResultsGroup>
<eCustomResults.01>99</eCustomResults.01>
<eCustomResults.02>MedHistoryOther</eCustomResults.02>
<eCustomResults.03>eHist</eCustomResults.03> <!--see eHistory.08 – use CorrelationID to extend eHistory.08 to this
custom element-->
</eCustomResults.ResultsGroup>
```

\*\*\*SUPPLEMENTAL\*\*\*

## Medical History Other

eCustomConfiguration.MedicalHistoryOtherStr

### Definition

Field used to pass a text/string value for Medical History Other.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

**Data Type**  
String

**minLength**  
1

**maxLength**  
50

### Data Element Comment

Field used to pass a text/string value for Medical History Other - should be used with MedHistoryOther field on previous page. This field will not populate unless MedHistoryOther is passed properly.

\*\*\*SUPPLEMENTAL\*\*\*

## Fire/First Responder

eCustomConfiguration.FirstResponder

### Definition

The Fire/First Responder code for this event.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

15

### Code List

Valid Fire/First Responder Import Value/code set up in myCARES.

### Data Element Comment

The values are unique to an agency and may comprise of a list of first responder names in the myCARES application. Lists can be obtained from the agency.

**\*\*CARES REQUIRED FIELD IN 2012\*\***



## Destination Hospital

eDisposition.02

### Definition

The destination hospital code for this event.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No (CARES) Yes (NEMSIS)
<b>Version 2 Element</b>	E20_02	<b>Is Nillable</b>	No (CARES) Yes (NEMSIS)
<b>Usage</b>	Required (CARES; see comments) Recommended (NEMSIS)	<b>Recurrence</b>	1:1

### Constraints

**Data Type**  
String

**minLength**  
2

**maxLength**  
50

### Code List

Valid Destination Hospital Import Value set up in myCARES.

### Data Element Comment

The values are unique to an agency and may comprise of a list of hospitals in the myCARES application, accessed through the code value passed in the import lists and can be obtained from the agency. If the patient is Pronounced in the Field (End of the Event), Destination Hospital is not required.

# ***EMS Dataset***

## ***Arrest Information***

## Location Type

eCustomConfiguration.LocationType

<b>Definition</b> The type of location where the incident occurred.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Home/Residence
2	Public/Commercial Building
3	Street/Hwy
4	Nursing Home
6	Healthcare Facility
9	Place of Recreation
10	Industrial Place
14	Other
15	Transport Center

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Location Type Other

eCustomConfiguration.LocationTypeOther

<b>Definition</b> The type of location where incident occurred; Other text field.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required (CARES; see comments) Optional (NEMSIS)	<b>Recurrence</b>	0:1

### Constraints

**Data Type**  
String

**minLength**  
1

**maxLength**  
50

### Data Element Comment

If Location Type = 14 (Other), this field is required. Otherwise, this is optional and only used to clarify location.

## Arrest Witnessed

eCustomConfiguration.ArrestWitnessed

### Definition

A witnessed arrest is one that is seen or heard by another person.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required	Recurrence	1:1

### Code List

Code	Description
------	-------------

1	Witnessed Arrest
2	Unwitnessed Arrest

### Data Element Comment

This field has been removed from CARES, however, myCares is still accepting this data.

eCustomConfiguration.ArrestWitnessed is mapped with eCustomConfiguration.ArrestAfterArrivalEMS to the new CARES field, Arrest Witnessed Status:

- Arrest Witnessed = Unwitnessed → Unwitnessed.
- Arrest Witnessed = Unwitnessed & Arrest After Arrival of 911 Responder = Blank → Unwitnessed.
- Arrest Witnessed = Witnessed & Arrest After Arrival of 911 Responder = Yes → Witnessed by 911 Responder.
- Arrest Witnessed = Witnessed & Arrest After Arrival of 911 Responder = No → Witnessed by Bystander.
- ELSE, Arrest Witness Status = blank.

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Arrest After Arrival of 911 Responder

eCustomConfiguration.ArrestAfterArrivalEMS

<b>Definition</b> Indicates if the patient arrested before or after the arrival of a 911 responder.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
------	-------------

1	Yes
2	No

### Data Element Comment

This field has been removed from CARES, however, myCares is still accepting this data.

eCustomConfiguration.ArrestAfterArrivalEMS is mapped with eCustomConfiguration.ArrestWitnessed to the new CARES field, Arrest Witnessed Status:

- Arrest Witnessed = Unwitnessed --> Unwitnessed.
- Arrest Witnessed = Unwitnessed & Arrest After Arrival of 911 Responder = Blank --> Unwitnessed.
- Arrest Witnessed = Witnessed & Arrest After Arrival of 911 Responder = Yes --> Witnessed by 911 Responder.
- Arrest Witnessed = Witnessed & Arrest After Arrival of 911 Responder = No --> Witnessed by Bystander.
- ELSE, Arrest Witness Status = blank.

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Presumed Cardiac Arrest Etiology

eArrest.02

### Definition

Indication of the etiology or cause of the cardiac arrest.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No (CARES) Yes (NEMSIS)
<b>Version 2 Element</b>	E11_02	<b>Is Nillable</b>	No (CARES) Yes (NEMSIS)
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
3002001	Presumed Cardiac Etiology
3002015	Trauma
3002013	Respiratory/Asphyxia
3002003	Drowning/Submersion
3002007	Electrocution
3002011	Other
3002009	Exsanguination/Hemorrhage
3002005	Drug Overdose

### Data Element Comment

See Custom Element CardiacEtiologyOther on next page for usage of “Other” values

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Presumed Cardiac Arrest Etiology Other

eCustomConfiguration.CardiacEtiologyOther

### Definition

Field used to pass a text/string value for Presumed Cardiac Arrest Etiology Other.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required (if value 3002011 passed in eArrest.02)	Recurrence	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

If value passed = 3002011, please pass a text value in CardiacEtiologyOther (required).



# ***EMS Dataset***

## ***Resuscitation Information***

## Resuscitation Attempted By 911 Responder (or AED shock given prior to EMS arrival)

eCustomConfiguration.ResusAttemptEMS

<b>Definition</b> Indication of an attempt to resuscitate the patient who is in cardiac arrest.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

**\*\*FIELD CHANGED IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Who Initiated CPR

eCustomConfiguration.InitiatedCPR

<b>Definition</b> Identifies the initial person to perform CPR.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Bystander
2	Family Member
3	First Responder
4	EMS Responder (transport EMS)
5	Healthcare Provider (non-911 Responder)
8	Not Applicable

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Did Law Enforcement initiate CPR?

eCustomConfiguration.InitiatedCPRLaw

### Definition

Identifies if the First Responder who was responsible for initiating CPR was Law Enforcement.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Required/Optional (see comments)	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

If **InitiatedCPR** equals First Responder (3), then it is required. Otherwise, a value should not be passed in the XML.

\*\*\*NEW FIELD IN NOVEMBER 2020\*\*\*

## Type of Bystander CPR Provided

eCustomConfiguration.BystanderCPRProvidedID

### Definition

Describes type of CPR (if) performed by a bystander.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Compressions and ventilations
2	Compressions only
3	Ventilations only
8	Unknown

### Data Element Comment

**\*\*NEW FIELD IN 2011\*\***

**\*\*\*SUPPLEMENTAL\*\*\***

## Were Dispatcher CPR instructions provided

### eCustomConfiguration.CPRInstructionsProvided

#### Definition

Indicates if dispatcher CPR instructions were provided to the caller.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

#### Code List

Code	Description
1	Yes
2	No
3	Unknown

#### Data Element Comment

**\*\*NEW FIELD IN 2011\*\***  
**\*\*\*SUPPLEMENTAL\*\*\***

## Was an AED applied prior to EMS arrival

eArrest.07

<b>Definition</b> Identifies if an AED was applied, with or without defibrillation, prior to the transporting provider's arrival on scene.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
3007001	No
3007003	Yes, without defibrillation
3007005	Yes, with defibrillation

### Data Element Comment

**\*\*NEW FIELD IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Who First Applied the AED

eCustomConfiguration.WhoFirstAppliedAED

### Definition

Identifies the individual who initially applied the AED during resuscitation.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	*No (see Comment)
<b>Version 2 Element</b>		<b>Is Nillable</b>	*No (see Comment)
<b>Usage</b>	*Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Bystander
2	Family Member
3	First Responder
6	Healthcare Provider (non-911 Responder)
10	Law Enforcement First Responder
11	Non-Law Enforcement First Responder

### Data Element Comment

\*If eArrest.07, Was an AED applied prior to EMS arrival = 3007001 (No), then any value passed in this field will be removed in parsing. In this case, please pass a nil and any NV in WhoFirstAppliedAED.

As of February 2017, Lay Person Medical Provider value has been changed from 5 to 6, but we will still accept the value of 5 for this field. No vendor intervention required. For vendors working on a new setup, please use 6 for this field.

PoliceAED is now mapped to Law/Non-Law Enforcement First Responder.

**\*\*CARES REQUIRED FIELD IN 2012\*\***



## Was AED first applied by Police

eCustomConfiguration.PoliceAED

### Definition

Identifies if the First Responder who initially applied/used the AED during the resuscitation was Police.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Required/Optional (CARES; see comments)	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

Used with WhoFirstAppliedAED. If the answer is First Responder (3) then this field is required, otherwise optional.

PoliceAED has been removed from the CARES form and is now mapped to Law/Non-Law Enforcement First Responder for WhoFirstAppliedAED.

**\*\*NEW FIELD IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Who First Defibrillated the Patient

eCustomConfiguration.FirstDefibPatient

### Definition

Identifies the individual who was responsible for first defibrillating the patient.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
1	Bystander
2	Family Member
3	First Responder (non-transport provider)
4	EMS Responder (transport EMS)
5	Healthcare Provider (non-911 Responder)
8	Not Applicable
10	Law Enforcement First Responder
11	Non-Law Enforcement First Responder

### Data Element Comment

PoliceDefib is now mapped to Law/Non-Law Enforcement First Responder.

**\*\*NEW FIELD IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Did the police first defibrillate the patient

eCustomConfiguration.PoliceDefib

### Definition

Identifies if the First Responder who was responsible for first defibrillating the patient was Police.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Required/Optional (see comments)	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

PoliceDefib has been removed from the CARES form and is now mapped to Law/Non-Law Enforcement First Responder for FirstDefibPatient.

Used with **FirstDefibPatient** if the answer is First Responder (3) then it is required, otherwise optional.

**\*\*NEW FIELD IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Did 911 Responder perform CPR

eCustomConfiguration.911RespCPR

### Definition

Indicates if 911 responder (BLS and/or ALS) performed CPR during the event.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

# ***EMS Dataset***

## ***First Cardiac/ROSC Information***

## First Arrest Rhythm of Patient (NEMSIS 3.3.4)

eCustomConfiguration.FirstRhythm

### Definition

The first monitored rhythm is the very first cardiac rhythm present when a manual (monitor/defibrillator) or AED (automated external defibrillator) is attached to a patient after cardiac arrest.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
------	-------------

0	Ventricular Fibrillation
1	Ventricular Tachycardia
2	Asystole
3	Idioventricular/PEA
6	Unknown Shockable Rhythm
7	Unknown Unshockable Rhythm

### Data Element Comment

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## First Arrest Rhythm of Patient (NEMSIS 3.4.0)

eArrest.11

### Definition

The first monitored rhythm is the first cardiac rhythm present when a manual (monitor/defibrillator) or AED (automated external defibrillator) is attached to a patient after cardiac arrest.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No (CARES) Yes (NEMSIS)
<b>Version 2 Element</b>	E11_05	<b>Is Nillable</b>	No (CARES) Yes (NEMSIS)
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
3011001	Asystole
3011005	PEA
3011007	Unknown AED Non-Shockable Rhythm
3011009	Unknown AED Shockable Rhythm
3011011	Ventricular Fibrillation
3011013	Ventricular Tachycardia-Pulseless

### Data Element Comment

Added term "Arrest" to title to clarify this is the arrest rhythm.

Values "Other" and "Normal Sinus Rhythm" removed since they are not Cardiac Arrest Rhythms.

Value "Ventricular Tachycardia" has been changed to "Ventricular Tachycardia-Pulseless".

This element is a component of the Utstein Cardiac Arrest Criteria as identified in the American Heart Association journal "Resuscitation" from 2004 entitled "Cardiac Arrest and Cardiopulmonary Resuscitation Outcome Reports".  
<http://circ.ahajournals.org/cgi/content/full/110/21/3385>

myCARES will not process Not Values for this field.

## Sustained ROSC (20 consecutive minutes)

Or present at end of EMS care

eCustomConfiguration.SustainedROSC

### Definition

Sustained Return of Spontaneous Circulation (ROSC) is defined as the restoration of a palpable pulse or a measurable blood pressure for 20 consecutive minutes or present at end of EMS care.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required	Recurrence	1:1

### Code List

Code	Description
------	-------------

2	No
3	Yes, but pulseless at end of EMS care (or ED arrival)
4	Yes, pulse at end of EMS care (or ED arrival)

### Data Element Comment

**\*\*FIELD CHANGED IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***



## End of the Event

eCustomConfiguration.EndOfEvent

### Definition

The reason that CPR or other resuscitation efforts were discontinued.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required	Recurrence	1:1

### Code List

Code	Description
------	-------------

- |   |                             |
|---|-----------------------------|
| 1 | Pronounced in the Field     |
| 2 | Pronounced in the ED        |
| 3 | Ongoing Resuscitation in ED |
| 4 | Effort ceased due to DNR    |

### Data Element Comment

**\*\*FIELD CHANGED IN 2011\*\***

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## When did sustained ROSC first occur

eCustomConfiguration.ROSCStart

### Definition

When ROSC (Return of Spontaneous Circulation) is defined as the restoration of a palpable pulse or a measurable blood pressure) first occurred.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Never
2	After Bystander CPR only
3	After Bystander defib shock
4	After EMS CPR only
5	After EMS Defib. shock
6	After ALS
7	Unknown

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

# ***EMS Dataset***

## ***Times Information***

## Estimated time of arrest

eArrest.14

<b>Definition</b> Estimated time of arrest.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E11_08	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

This field is mapped to eArrest.14, which is required if using for Date of Arrest. This myCARES time field is captured separately and optional.

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time of 1<sup>st</sup> defibrillatory shock

eCustomConfiguration.DefibTime

<b>Definition</b> The time the first defibrillation was given.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time of 1<sup>st</sup> CPR (NEMESIS 3.3.4)

eCustomConfiguration.CPRTIME

<b>Definition</b> The time CPR was first given (by anyone).			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy	a four-digit numeral that represents the year
'-'	separators between parts of the date portion
mm	a two-digit numeral that represents the month
dd	a two-digit numeral that represents the day
T	separator that indicates time-of-day follows
hh	a two-digit numeral that represents the hour
':'	a separator between parts of the time-of-day portion
mm	a two-digit numeral that represents the minute
ss	a two-integer-digit numeral that represents the whole seconds
'.' s+	(not required) represents the fractional seconds
zzzzzz	(required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

Time of 1<sup>st</sup> CPR (NEMESIS 3.4.0)

eArrest.19

<b>Definition</b> The initial date and time that CPR was started by anyone.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

Constraints

<b>Data Type</b>	<b>minInclusive</b>	<b>maxInclusive</b>
dateTime	1950-01-01T00:00:00-00:00	2050-01-01T00:00:00-00:00

**Pattern**  
[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Time of Sustained ROSC

eCustomConfiguration.TimeSusRosC

<b>Definition</b> The time of sustained ROSC.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*



## Time Resuscitation Terminated

eArrest.15

<b>Definition</b> The date/time resuscitation was terminated.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## No First Responder dispatched

eCustomConfiguration.NoFRDisp

### Definition

Custom field - single checkbox. Indicates that a 911 first responder was not dispatched.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	Yes (NEMSIS) No (CARES)
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	True

### Data Element Comment

Not Values passed are not mapped.

\*\*\*SUPPLEMENTAL\*\*\*

## Time call received at dispatch center

eTimes.01

<b>Definition</b> The time the original call was received at the dispatch center.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_02	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

This date/time might be the same as Dispatch Notified Date/Time (eTimes.02).

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time First Responder dispatched

eCustomConfiguration.FRDispatched

<b>Definition</b> The time the first responder was dispatched to arrive on scene.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time First Responder en route

eCustomConfiguration.FREnroute

<b>Definition</b> The time the first responder vehicle began moving towards the scene.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

<b>Data Type</b>	<b>minInclusive</b>	<b>maxInclusive</b>
dateTime	1950-01-01T00:00:00-00:00	2050-01-01T00:00:00-00:00

### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy	a four-digit numeral that represents the year
'-'	separators between parts of the date portion
mm	a two-digit numeral that represents the month
dd	a two-digit numeral that represents the day
T	separator that indicates time-of-day follows
hh	a two-digit numeral that represents the hour
':'	a separator between parts of the time-of-day portion
mm	a two-digit numeral that represents the minute
ss	a two-integer-digit numeral that represents the whole seconds
'.' s+	(not required) represents the fractional seconds
zzzzzz	(required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time First Responder arrived at scene

eCustomConfiguration.FROnscene

<b>Definition</b> The time the first responder arrived at scene.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

<b>Data Type</b>	<b>minInclusive</b>	<b>maxInclusive</b>
dateTime	1950-01-01T00:00:00-00:00	2050-01-01T00:00:00-00:00

### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy	a four-digit numeral that represents the year
'-'	separators between parts of the date portion
mm	a two-digit numeral that represents the month
dd	a two-digit numeral that represents the day
T	separator that indicates time-of-day follows
hh	a two-digit numeral that represents the hour
':'	a separator between parts of the time-of-day portion
mm	a two-digit numeral that represents the minute
ss	a two-integer-digit numeral that represents the whole seconds
'.' s+	(not required) represents the fractional seconds
zzzzzz	(required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time Ambulance dispatched

eTimes.03

<b>Definition</b> The time the ambulance (transporting provider) was dispatched to arrive on scene.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No
<b>Version 2 Element</b>	E05_04	<b>Is Nillable</b>	No
<b>Usage</b>	Mandatory (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

If servicedate and eArrest.14 are nil/missing, this value will be used for Date of Arrest.

Since this element is not nillable and does not accept NV- please pass min value if no mapping to this field

1950-01-01T00:00:0000:00

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*



## Time Ambulance en route

eTimes.05

<b>Definition</b> The time the ambulance (transporting provider) vehicle began moving towards the scene.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_05	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time Ambulance arrived at scene

eTimes.06

<b>Definition</b> The time the ambulance (transporting provider) arrived at scene.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_06	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

This date/time might be the same as Dispatch Notified Date/Time (eTimes.02).

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time EMS arrived at patient side

eTimes.07

<b>Definition</b> The time the ambulance (transporting provider) vehicle arrived at the patient's side.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_07	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

This date/time might be the same as Dispatch Notified Date/Time (eTimes.02).

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time Ambulance left scene

eTimes.09

<b>Definition</b> The time the ambulance (transporting provider) left the scene.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_09	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Time Ambulance arrived at ED

eTimes.11

<b>Definition</b> The time the ambulance (transporting provider) arrived at the destination hospital's ED.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E05_10	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy a four-digit numeral that represents the year  
 '-' separators between parts of the date portion  
 mm a two-digit numeral that represents the month  
 dd a two-digit numeral that represents the day  
 T separator that indicates time-of-day follows  
 hh a two-digit numeral that represents the hour  
 ':' a separator between parts of the time-of-day portion  
 mm a two-digit numeral that represents the minute  
 ss a two-integer-digit numeral that represents the whole seconds  
 '.' s+ (not required) represents the fractional seconds  
 zzzzzz (required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh a two-digit numeral (with leading zeros as required) that represents the hours  
 mm a two-digit numeral that represents the minutes  
 '+' a nonnegative duration  
 '-' a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

# ***EMS Dataset***

## ***Hypothermia Information***

## Was hypothermia care provided in the field (NEMSIS 3.3.4)

eArrest.10

### Definition

Documentation of EMS initiation of therapeutic hypothermia prior to ED arrival.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No (CARES) Yes (NEMSIS)
<b>Version 2 Element</b>	E11_05	<b>Is Nillable</b>	No (CARES) Yes (NEMSIS)
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Code List

Code	Description
9923001	No
9923003	Yes

### Data Element Comment

**\*\*REQUIRED FIELD IN 2011\*\***



## Was hypothermia care provided in the field (NEMSIS 3.4.0)

eProcedures.03

### Definition

The procedure - Hypothermia Induction Therapy (includes cooled IV fluids) - performed on the patient.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E19_03	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required	<b>Recurrence</b>	1:1

### Attributes

#### Pertinent Negatives (PN)

8801001 - Contraindication Noted 8801003 - Denied By Order 8801019 – Refused  
8801023 - Unable to Complete

### Code List

#### Code

#### Description

430189000 Hypothermia Induction Therapy (includes cooled IV fluids)

### Data Element Comment

A SNOMED code of 430189000 will map to Yes in CARES. A PN value will map to No in CARES.

If the agency cannot capture a PN for this field, there is an agency setup item in CARES to default blank or nil to "No" for all records. Please contact your CARES liaison in order to activate this checkbox.

### SNOMEDCT

Website: [http://www.nlm.nih.gov/research/umls/Snomed/snomed\\_main.html](http://www.nlm.nih.gov/research/umls/Snomed/snomed_main.html)

Product: Product - UMLS Metathesaurus

**\*\*REQUIRED FIELD IN 2011\*\***

# ***EMS Dataset***

## ***EMS Interventions***

## Mechanical CPR device used (NEMSIS 3.3.4)

eCustomConfiguration.MechCPRDevice

### Definition

Indicates if a mechanical CPR device was used during the course of resuscitation in the field.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Mechanical CPR device used (NEMSIS 3.4.0)

eProcedures.03

### Definition

Indicates if a mechanical CPR device was used during the course of resuscitation in the field.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	E19_03	<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1(CARES) 1:1(NEMSIS)

### Attributes

#### Pertinent Negatives (PN)

8801001 - Contraindication Noted 8801003 - Denied By Order 8801019 – Refused  
8801023 - Unable to Complete

### Code List

Code	Description
429283006	CPR Mechanical Device

### Data Element Comment

A SNOMED code of 429283006 will map to Yes in CARES. A PN value will map to No in CARES.

SNOMEDCT

Website: [http://www.nlm.nih.gov/research/umls/Snomed/snomed\\_main.html](http://www.nlm.nih.gov/research/umls/Snomed/snomed_main.html)

Product: Product - UMLS Metathesaurus

\*\*\*SUPPLEMENTAL\*\*\*

## Mechanical CPR device used detail

eCustomConfiguration.MechCPRDeviceID

### Definition

Associated with Mechanical CPR device used, if yes, specify which device was used.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Load-Distributing Band (AutoPulse)
2	Active Compression Decompression (LUCAS™ Device)
3	Mechanical Piston
4	Other

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Automated CPR feedback device used

eCustomConfiguration.CPRFeedbackDevice

### Definition

Indicates if an automated CPR feedback device was used during the course of resuscitation in the field.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Advanced airway successfully placed in the field

eAirway.02

<b>Definition</b> The date and time the airway device placement was confirmed.			
<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	Yes	<b>NOT Values</b>	No (CARES) Yes (NEMSIS)
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Recommended (NEMSIS) Optional (CARES)	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

This field maps to a xs:dateTime NEMSIS field eAirway.02. **To use eAirway.03, you must pass a datetime value in this field.** If the exact time is not known, pass servicedate with midnight. The logic for the answer choice "No" really means the airway attempt was "Unsuccessful" and that the airway placement was attempted. It does NOT mean that the question was not applicable, not documented, etc. Not Values for this field will not be mapped.

eAirway.02 (Was advanced airway placed successfully in the field) is of datetime type. If you pass a date for this greater than the minInclusive value for this element, we will record this as a "Yes" answer. If you pass the minInclusive value of 1950-01-01T00:00:00-00:00 we will record a "No".

Examples:

**Pass a "No" value:**

<eAirway.02>1950-01-01T00:00:00-00:00</eAirway.02>

**Pass a "Yes" with Combitude value**

<eAirway.02>2013-06-04T00:00:00-08:00</eAirway.02>

<eAirway.03>4003007</eAirway.03>

\*\*\*SUPPLEMENTAL\*\*\*

## Advanced airway successfully placed in the field detail

eAirway.03

### Definition

Associated with Advanced Airway Successfully Placed in the Field, if yes, specify which device was used.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	Yes
Version 2 Element		Is Nillable	Yes
Usage	Recommended (NEMSIS) Optional (CARES)	Recurrence	1:M

### Attributes

#### NOT Values

7701001 - Not Applicable 7701003 - Not Recorded 7701005 - Not Reporting

### Code List

Code	Description
------	-------------

4003007	Combitube
4003009	King airway
4003011	LMA
4003003	Oral/Nasal ET
4003001	Maps to Other radio and Cricothyrotomy Tube to other text field in CARES
4003013	Maps to Other radio and SAD-Other to other text field in CARES
4003015	Maps to "Used existing tracheostomy" for primary question, Advanced Airway successfully placed in field, in CARES
4003005	Maps to Other radio and Other-Invasive Airway to other text field in CARES

### Data Element Comment

To use this field, you must pass a datetime value for eAirway.02. The descriptions for those items that map to "Other" in myCARES above will be saved in the Advanced Airway "Other" text field in the myCARES Rev4 form.

\*\*\*SUPPLEMENTAL\*\*\*



## Airway Other

eCustomConfiguration.AirwayOtherStr

### Definition

Field used to pass a text/string value for Airway Other.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

100

### Data Element Comment

Field used to pass a text/string value for Airway Other

\*\*\*SUPPLEMENTAL\*\*\*

## ITD used (NEMESIS 3.3.4)

eCustomConfiguration.ITD

### Definition

Indicates whether an ITD (Impedance Threshold Device) was used during resuscitation.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
------	-------------

1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

**Definition**

Indicates whether an ITD (Impedance Threshold Device) was used during resuscitation as a procedure.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMESIS) No (CARES)
<b>Version 2 Element</b>	E19_03	<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

**Attributes**
**Pertinent Negatives (PN)**

8801001 - Contraindication Noted 8801003 - Denied By Order 8801019 – Refused  
8801023 - Unable to Complete

**Code List**

<b>Code</b>	<b>Description</b>
441893003	Impedance Threshold Device

**Data Element Comment**

A SNOMED code of 441893003 will map to Yes in CARES. A PN value will map to No in CARES.

SNOMEDCT

Website: [http://www.nlm.nih.gov/research/umls/Snomed/snomed\\_main.html](http://www.nlm.nih.gov/research/umls/Snomed/snomed_main.html)

Product: Product - UMLS Metathesaurus

**\*\*\*SUPPLEMENTAL\*\*\***

## ITD used detail

eCustomConfiguration.ITDID

### Definition

If the device is used during resuscitation, the type of device should be indicated. If ITD = Yes, then indicate the device.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	Yes (NEMSIS) No (CARES)
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Bag valve mask
<del>2</del>	<del>Endotracheal tube</del>
3	Combitube
4	King Airway
5	LMA
6	Oral/Nasal ET
7	Other

### Data Element Comment

2 - Endotracheal tube now mapped to 6 – Oral/Nasal ET

\*\*\*SUPPLEMENTAL\*\*\*

## ITD Used Other

eCustomConfiguration.ITDOtherStr

### Definition

Field used to pass a text/string value for Impedance Threshold Device Other.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Optional	Recurrence	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

Field used to pass a text/string value for Impedance Threshold Device Other

\*\*\*SUPPLEMENTAL\*\*\*

## Were drugs administered

eCustomConfiguration.DrugAdministration

### Definition

Indicates whether drugs were administered during field resuscitation.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Were drugs administered detail

eMedications.03

### Definition

Indicates specific drugs that were administered during field resuscitation.

<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMSIS) No (CARES)
<b>Version 2 Element</b>	<b>E18_03</b>	<b>Is Nillable</b>	Yes
<b>Usage</b>	Required (NEMSIS) Optional (CARES)	<b>Recurrence</b>	1:M

### Code List (RXNorm)

Code	Description
317361	Epinephrine 0.1mg/ml
1223	Atropine
703	Amiodarone
36676	Sodium Bicarbonate
237653	Dextrose
6387	Lidocaine
11149	Vasopressin
1901	Calcium Chloride
6585	Magnesium Sulfate

### *The following RXNorm codes map to myCARES Naloxone:*

1725055	1870932	7242
1725056	1870933	197117
1725057	1870934	203192
1725058	1870935	
1725059		
1725060		
1725061		
1725062		
1725063		
1725064		

### Data Element Comment

To pass "Other"- refer to custom element MedicationOther, all other codes are from RXNorm.

To pass "Other" medication, correlate this element to custom element in the group tag.

<eMedications.MedicationGroup CorrelationID="eMed">

\*\*\*SUPPLEMENTAL\*\*\*

## Were drugs administered detail – Other

eCustomConfiguration.MedicationOther

### Definition

Indicates that other drugs were administered during field resuscitation.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
099	Other

### Data Element Comment

```
<eCustomResults.ResultsGroup>
<eCustomResults.01>099</eCustomResults.01>
<eCustomResults.02>MedicationOther</eCustomResults.02>
<eCustomResults.03>eMed</eCustomResults.03>
</eCustomResults.ResultsGroup>
```

\*\*\*SUPPLEMENTAL\*\*\*



## Were drugs administered detail – Other

eCustomConfiguration.MedicationOtherStr

### Definition

Field used to pass a text/string value for Were drugs administered detail - Other.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

String

#### minLength

1

#### maxLength

50

### Data Element Comment

If value passed = 099 for MedicationOther, a text value may be passed in MedicationOtherStr in order to list other drugs administered during field resuscitation that are not included in the myCares accepted list for eMedications.03.

\*\*\*SUPPLEMENTAL\*\*\*

## Vascular access

eCustomConfiguration.VascularAccessID

### Definition

Describes which, if any, devices were inserted into a vein, which permits administration of intermittent or continuous infusion of parenteral solutions or medications.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:M

### Code List

Code	Description
1	No IV
2	IV
3	IO
4	None

### Data Element Comment

No IV removed from CARES form.

\*\*\*SUPPLEMENTAL\*\*\*

## 12 Lead (NEMSIS 3.3.4)

eCustomConfiguration.12Lead

### Definition

Indicates use of a 12 Lead. A 12 Lead electrocardiogram (ECG) is a recording of the electrical activity of the heart using specific wires (leads) placed on the chest wall and extremities.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## 12 Lead (NEMESIS 3.4.0)

eProcedures.03

<b>Definition</b> 12 Lead ECG obtained as a procedure.			
<b>National Element</b>	Yes	<b>Pertinent Negatives (PN)</b>	Yes
<b>State Element</b>	Yes	<b>NOT Values</b>	Yes (NEMESIS) No (CARES)
<b>Version 2 Element</b>	E19_03	<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Attributes

#### Pertinent Negatives (PN)

8801001 - Contraindication Noted   8801003 - Denied By Order   8801019 – Refused  
8801023 - Unable to Complete

### Code List

Code	Description
268400002	12 Lead ECG Obtained

### Data Element Comment

A SNOMED code of 268400002 will map to Yes in CARES. A PN value will map to No in CARES.

SNOMEDCT

Website: [http://www.nlm.nih.gov/research/umls/Snomed/snomed\\_main.html](http://www.nlm.nih.gov/research/umls/Snomed/snomed_main.html)

Product: Product - UMLS Metathesaurus

\*\*\*SUPPLEMENTAL\*\*\*

## STEMI

eCustomConfiguration.STEMI

### Definition

Indicates a myocardial infarction with ST elevation.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No
3	Unknown

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

# ***Hospital Dataset***

## ***Hospital Information***

## Passing Destination Hospital and Transfer Hospital data

Hospital information in an import may provide outcome data for *either* a destination or a transfer hospital the following ways. The hospital form fields are interdependent and must follow the below logic.

### Transfer with Complete or Partial Hospital Outcome Data from Transfer Hospital:

*Destination Hospital Elements and Data (no other element values will be parsed)*

- EROutcome must = 4 (Transferred)
- Hypothermia\_Provided\_Hosp can be answered
- Transfer\_hospitalid or Transfer\_hospital should be answered

*Transfer Hospital Elements and Data*

- If EROutcomeTrans = 5, the following elements can contain values:
  - HospOutcomeTrans can be answered
  - HospOutcomeDNRTans can be answered
  - If HospOutcomeTrans or HospOutcomeDNRTans = 2, the following fields may contain values
    - HospDispositionTrans
    - NeuroOutcomeTrans can be answered if there is a value for HospDispositionTrans

### Hospital Data for Destination Hospital ONLY:

*Destination Hospital Elements and Data*

- EROutcome must not = 4 (Transferred)
- Hypothermia\_Provided\_Hosp can be answered
- HospOutcome can be answered
- HospOutcomeDNR can be answered
- eOutcome.02 can be answered if ER or HospOutcome = Discharged Alive
- eArrest.13 can be answered if ER or HospOutcome = Discharged Alive and eOutcome.02 contains a value
- Transfer\_hospitalid or Transfer\_hospital should be answered only if HospOutcome or HospOutcomeDNR = Transferred
- If HospOutcome or HospOutcomeDNR = Transferred, eOutcome.02 and eArrest.13 will not be parsed

*Transfer Hospital Elements and Data*

- None of these elements for transfer hospital will be parsed

### Supplemental Hospital Elements:

- For eCustomConfiguration hospital elements: MyocardialInfarction, CoronaryAngiography/CoronaryAngiographyDateTime, CardiacStent, CABGPerformed, and ICDPlaced only the affirmative response between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative for both hospitals, then the response from the final destination hospital should be passed.

## Emergency Room Outcome (Destination Hospital) eCustomConfiguration.EROutcome

### Definition

The final disposition of the patient from the emergency department.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Died in the ED
4	Transferred to another acute care facility from the ED
5	Admitted to hospital

### Data Element Comment

This element is used for the destination hospital only.

See EROutcomeTransfer element if value = 4 (Transferred). If value = 4, please use the Transfer Hospital fields. You may pass values for Hypothermia\_Provided\_Hosp for the Destination Hospital and should pass either Transfer\_hospitalId or Transfer\_Hospital values, but values passed in the following elements will not be parsed:

- HospOutcome
- HospOutcomeDNR
- eOutcome.02
- eArrest.13

**\*\*FIELD CHANGED IN 2011\*\***



## Was hypothermia/TTM care initiated or continued in the hospital (Destination Hospital)

eCustomConfiguration.Hypothermia\_Provided\_Hosp

### Definition

Indicates whether hypothermia care was initiated or continued in the destination hospital.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Yes
2	No

## Hospital Outcome (Destination Hospital)

eCustomConfiguration.HospOutcome

### Definition

The final disposition of the patient from the hospital. See HospOutcomeDNR if value = 4 (Patient made DNR).

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Died in the hospital
2	Discharged Alive
3	Transferred to another acute care hospital
4	Patient made DNR
11	Not yet determined

### Data Element Comment

If the value passed is 3 (Transferred to another acute care hospital) or the value passed is 4 and HospOutcomeDNR is 3 (Transferred to another acute care hospital), any values passed for eOutcome.02 and eArrest.13 are not parsed. The Transfer Hospital must enter in these values manually.

**\*\*FIELD CHANGED IN 2011\*\***

## Patient made DNR Detail (Destination Hospital) eCustomConfiguration.HospOutcomeDNR

### Definition

Custom field associated with Hospital Outcome (HospOutcome). If Patient made DNR (code = 4), identify hospital outcome.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Died in the hospital
2	Discharged alive
3	Transferred to another acute care hospital
8	Not yet determined

### Data Element Comment

If HospOutcome value passed is 3 (Transferred to another acute care hospital) or the value passed is 4 and HospOutcomeDNR is 3 (Transferred to another acute care hospital), any values passed for eOutcome.02 and eArrest.13 are not parsed. The Transfer hospital must enter in these values manually.

**\*\*NEW FIELD IN 2011\*\***

## Discharge From the Hospital (Destination Hospital)

eOutcome.02

### Definition

This element's value is only recorded if the HospOutcome or HospOutcomeDNR value = "Discharged alive". Type of location patient discharged to from the hospital for Destination Hospital ONLY.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
01	Home/Residence
62	Rehabilitation facility
03	Skilled nursing facility/Hospice
51	Skilled nursing facility/Hospice

### Data Element Comment

Discharge status from the hospital for Destination Hospital ONLY.

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Neurological Outcome at Discharge From Hospital (Destination Hospital)

eArrest.13

### Definition

Neurological outcome status or cerebral performance level at discharge for Destination Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element	E11_07	Is Nillable	No
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
3013001	Good Cerebral Performance (CPC 1)
3013003	Moderate Cerebral Disability (CPC 2)
3013005	Severe Cerebral Disability (CPC 3)
3013007	Coma, vegetative state (CPC 4)

### Data Element Comment

This element's value is only recorded if the HospOutcome or HospOutcomeDNR value = "Discharged alive" and eOutcome.02 contains a value.

**\*\*FIELD CHANGED IN 2011\*\***

## Emergency Room Outcome (Transfer Hospital) eCustomConfiguration.EROutcomeTrans

### Definition

The final disposition of the patient from the emergency department for the Transfer Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Resuscitation terminated in ED
4	Transferred to another acute care facility from the ED
5	Admitted to hospital

### Data Element Comment

This element is used for the transfer hospital and is *only* used if the EROutcome value for destination hospital = 4.

## Hospital Outcome (Transfer Hospital)

eCustomConfiguration.HospOutcomeTrans

### Definition

The final disposition of the patient from the hospital for the Transfer Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Died in the hospital
2	Discharged Alive
3	Transferred to another acute care hospital
4	Patient made DNR
11	Not yet determined

### Data Element Comment

If the HospitalOutcomeTrans value passed is 3 (Transferred to another acute care hospital) or the value passed is 4 and HospOutcomeDNR is 3 (Transferred to another acute care hospital), any values passed for NeuroOutcomeTrans and HospDispositionTrans are not parsed. The Transfer hospital must enter in these values manually.

See follow-up question HospOutcomeDNRTans if value = 4 (Patient made DNR).

**\*\*FIELD CHANGED IN 2011\*\***

## Patient made DNR Detail (Transfer Hospital)

eCustomConfiguration.HospOutcomeDNRTrans

### Definition

Custom field associated with Hospital Outcome (HospOutcomeTrans = 4).

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	No
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Died in the hospital
2	Discharged alive
3	Transferred to another acute care hospital
8	Not yet determined

### Data Element Comment

If HospOutcomeTrans value passed is 3 (Transferred to another acute care hospital) or the value passed is 4 and HospOutcomeDNRTrans is 3 (Transferred to another acute care hospital), any values passed for NeuroOutcomeTrans and HospDispositionTrans are not parsed. The Transfer Hospital must enter in these values manually.

**\*\*NEW FIELD IN 2011\*\***



## Discharge From the Hospital (Transfer Hospital)

eCustomConfiguration.HospDispositionTrans

### Definition

Type of location patient discharged to from the hospital for Transfer Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Required	Recurrence	0:1

### Code List

Code	Description
01	Home/Residence
62	Rehabilitation facility
03	Skilled nursing facility/Hospice
51	Skilled nursing facility/Hospice

### Data Element Comment

This element's value is only recorded if the HospOutcomeTrans or HospOutcomeDNRTans value = "Discharged alive".

**\*\*CARES REQUIRED FIELD IN 2012\*\***

## Neurological Outcome at Discharge From Hospital (Transfer Hospital)

eCustomConfiguration.NeuroOutcomeTrans

### Definition

Neurological outcome status or cerebral performance level at discharge for Transfer Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	No
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
3013001	Good Cerebral Performance (CPC 1)
3013003	Moderate Cerebral Disability (CPC 2)
3013005	Severe Cerebral Disability (CPC 3)
3013007	Coma, vegetative state (CPC 4)

### Data Element Comment

This element's value is only recorded if the HospOutcomeTrans or HospOutcomeDNRTans value = "Discharged alive" and HospDispositionTrans contains a value.

**\*\*FIELD CHANGED IN 2011\*\***

## Was hypothermia/TTM care initiated or continued in the hospital (Transfer Hospital)

eCustomConfiguration.Hypothermia\_Provided\_Hosp\_Trans

### Definition

Was hypothermia care initiated or continued in the Transfer Hospital ONLY.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

**\*\*REQUIRED FIELD IN 2011\*\***

## Transfer To Hospital

eCustomConfiguration.Transfer\_hospitalid

### Definition

The hospital the patient was transferred to from Destination Hospital.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Hospital code patient was transferred to (CARES code).

### Data Element Comment

Must be a valid hospital import value set up in myCares.net.

## Transfer To Hospital - Detail

eCustomConfiguration,Transfer\_hospital

### Definition

If the hospital code patient was transferred to (CARES code) is not available, then this string would be the name of the hospital. See Transfer\_hospitalid custom element.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Data Type

String

### Data Element Comment

If the hospital (import value) patient was transferred to (CARES code) is not available, then this string would be the name of the hospital.

## Why was hypothermia/TTM care not initiated or continued in the hospital?

eCustomConfiguration.HypoNotInitiatedHosp

### Definition

Hospital data - Indicates the reason that hypothermia care was not initiated or continued in the hospital setting.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Awake/Following commands
2	DNR/Family Request
3	Unwitnessed Cardiac Arrest
4	Unshockable Rhythm
5	No TH program in place
8	Unknown
9	Other

### Data Element Comment

\*\*\*SUPPLEMENTAL\*\*\*

## Date/Time of Discharge/Death

eCustomConfiguration.DischargeDeathDateTime

Definition			
Hospital Data - The date and time of patient's discharge from the hospital or death.			
National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Constraints

Data Type	minInclusive	maxInclusive
dateTime	1950-01-01T00:00:00-00:00	2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy	a four-digit numeral that represents the year
'-'	separators between parts of the date portion
mm	a two-digit numeral that represents the month
dd	a two-digit numeral that represents the day
T	separator that indicates time-of-day follows
hh	a two-digit numeral that represents the hour
':'	a separator between parts of the time-of-day portion
mm	a two-digit numeral that represents the minute
ss	a two-integer-digit numeral that represents the whole seconds
'.' s+	(not required) represents the fractional seconds
zzzzzz	(required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Was the final diagnosis acute myocardial infarction

eCustomConfiguration.MyocardialInfarction

### Definition

Hospital Data - Indicates whether the final diagnosis was acute myocardial infarction.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No

### Data Element Comment

Only the affirmative response (Yes) between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative (No) for both hospitals, then the response from the final destination hospital should be passed.

\*\*\*SUPPLEMENTAL\*\*\*



## Coronary Angiography Performed

eCustomConfiguration.CoronaryAngiography

### Definition

Hospital Data - Indicates whether a Coronary Angiography was performed.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Yes
2	No
3	Unknown

### Data Element Comment

Only the affirmative response (Yes) and associated Date/Time value between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative (No) for both hospitals, then the response from the final destination hospital should be passed.

\*\*\*SUPPLEMENTAL\*\*\*

## Coronary Angiography Date/Time

eCustomConfiguration.CoronaryAngiographyDateTime

### Definition

Hospital Data - If Coronary Angiography Performed is yes, provide date and time.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

#### Data Type

dateTime

#### minInclusive

1950-01-01T00:00:00-00:00

#### maxInclusive

2050-01-01T00:00:00-00:00

#### Pattern

[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(\.\d+)?(\+|-)[0-9]{2}:[0-9]{2}

### Data Element Comment

Only the affirmative response (Yes) for Coronary Angiography Performed and associated Date/Time value between the Destination Hospital and Transfer Hospital should be passed. If there is a Date/Time value for both hospitals, then the Date/Time value from the final destination hospital should be passed. If the Coronary Angiography Performed response is negative (No) for both hospitals, then no Date/Time value needs to be passed from either hospital.

DateTime consists of finite-length characters of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss ('.' s+)? (zzzzzz)

yyyy	a four-digit numeral that represents the year
'-'	separators between parts of the date portion
mm	a two-digit numeral that represents the month
dd	a two-digit numeral that represents the day
T	separator that indicates time-of-day follows
hh	a two-digit numeral that represents the hour
':'	a separator between parts of the time-of-day portion
mm	a two-digit numeral that represents the minute
ss	a two-integer-digit numeral that represents the whole seconds
'.' s+	(not required) represents the fractional seconds
zzzzzz	(required) represents the timezone (as described below)

Timezones, required, are durations with (integer-valued) hour and minute properties in the form: ('+' | '-') hh ':' mm

hh	a two-digit numeral (with leading zeros as required) that represents the hours
mm	a two-digit numeral that represents the minutes
'+'	a nonnegative duration
'-'	a nonpositive duration

\*\*\*SUPPLEMENTAL\*\*\*

## Was a cardiac stent placed

eCustomConfiguration.CardiacStent

### Definition

Hospital Data – Indicates whether a cardiac stent was placed.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Yes
2	No
3	Unknown

### Data Element Comment

Only the affirmative response (Yes) between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative (No) for both hospitals, then the response from the final destination hospital should be passed.

\*\*\*SUPPLEMENTAL\*\*\*

## CABG performed

eCustomConfiguration.CABGPerformed

### Definition

Hospital Data – Indicates whether a Coronary Artery Bypass Graft was performed.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Code List

Code	Description
1	Yes
2	No
3	Unknown

### Data Element Comment

Only the affirmative response (Yes) and associated Date/Time value between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative (No) for both hospitals, then the response from the final destination hospital should be passed.

\*\*\*SUPPLEMENTAL\*\*\*

## Was an ICD placed and/or scheduled

eCustomConfiguration.ICDPlaced

### Definition

Hospital Data – Indicates whether an ICD placed and/or scheduled.

National Element	No	Pertinent Negatives (PN)	No
State Element	No	NOT Values	No
Version 2 Element		Is Nillable	Yes
Usage	Optional	Recurrence	0:1

### Code List

Code	Description
1	Yes
2	No
3	Unknown

### Data Element Comment

Only the affirmative response (Yes) and associated Date/Time value between the Destination Hospital and Transfer Hospital should be passed. If the response is affirmative for both hospitals, then the response from the final destination hospital should be passed. If the response is negative (No) for both hospitals, then the response from the final destination hospital should be passed.

\*\*\*SUPPLEMENTAL\*\*\*

## Hospital Medical Record Number

eOutcome.03/eOutcome.04

### Definition

Hospital data - The unique number assigned by the hospital for each patient's Medical Record.

<b>National Element</b>	No	<b>Pertinent Negatives (PN)</b>	No
<b>State Element</b>	No	<b>NOT Values</b>	No
<b>Version 2 Element</b>		<b>Is Nillable</b>	Yes
<b>Usage</b>	Optional	<b>Recurrence</b>	0:1

### Constraints

**Data Type**  
String

**minLength**  
0

**maxLength**  
30

### Data Element Comment

This was mapped to eCustomConfiguration.HospMedicalRecordNo but now is pulled from eOutcome.04 if eOutcome.03 = 4303005 Hospital - Receiving

\*\*\*SUPPLEMENTAL\*\*\*

## Index

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------



<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

<u>Data Element</u>	<u>Number</u>	<u>Page</u>
---------------------	---------------	-------------

